

PRODUKTBLAD

PA-2700 DAS Slutsteg

PA-2700 DAS Slutsteg

- 1350 W x 1350 W at 4 ?
- Input Sensitivity Selector
- Stereo/Bridged/Parallel Operation
- speakON output connectors
- Clip, protection and Signal present LED indicators

The PA series amplifiers are designed and built to provide an affordable, quality powering solution. The wide range of models makes the series ideal for both installed or mobile sound reinforcement applications. The amplifiers incorporate a rugged 2 unit all-steel chassis ensuring structural rigidity. The low-noise fans offer both quiet and cool operation. The amplifier incorporates rear located switches which permit, operational mode selection (bridge, stereo or parallel) and input sensitivity selection.

Stereo Mode (both channels driven)

8 ohms EIA 1 kHz 1% THD

1000 W

4 ohms EIA 1 kHz 1% THD

1350 W

Bridge Mono Mode

8 ohms EIA 1 kHz 1% THD

2700 W

Frequency Response

20 Hz-20 kHz +0-1 dB

Signal to Noise Ratio (20 Hz-20 kHz)



SAC Nordic AB • Prästtorpsvägen 16 • S-341 51 Lagan • SWEDEN • www.sacnordic.com

Safe Security Solutions

PRODUKTBLAD

PA-2700 DAS Slutsteg

> 100 dB

Distortion (SMPTE-IM)

? 0.35%

Total Harmonic Distortion (20 Hz-20 kHz)

? 0.35%

Damping Factor @ 8 ohms

> 200

Input Sensitivity @ 4 ohms

0.775 V o 1.4 V

Voltage Gain

36 dB

AC Requirements 230 V AC

50 Hz

Art.nr	E-nummer	Modell	Beskrivning	Mått i mm	Vikt
--------	----------	--------	-------------	-----------	------

9.2 A

Dimensions (H x W x D)

88 x 482 x 294 mm

Weight

19.5 kg



SAC Nordic AB • Prästtorpsvägen 16 • S-341 51 Lagan • SWEDEN • www.sacnordic.com

Safe Security Solutions